

CLAIMS

We claim:

1) A method, comprising:

optimizing an implementation of a programming language, comprising;
analyzing one or more values computed by a program written in the
programming language, wherein analyzing one or more values
comprises;
representing each bit within a value of the one or more values as an
abstract element of a lattice having a set of abstract elements
including 0_A , 1_A , \perp_A and T_A , wherein the lattice is an abstraction of a
concrete domain containing 0, 1, and \perp ;
analyzing one or more output bits that are produced by an operation in
terms of one or more input bits that are input to the operation; and
analyzing the input bits that are input to the operation in terms of the
output bits that are produced by the operation.

2). The method of claim 1, wherein optimizing further comprises:

applying a forward abstract semantic to the abstract element; and
applying a backward abstract semantic to the abstract element;
wherein the forward abstract semantic is an approximation of a forward
concrete semantic including AND, OR, and NOT; and
wherein the backward abstract semantic is an approximation of a backward
concrete semantic including AND^{-1} , OR^{-1} , and NOT^{-1} .

3). The method of claim 2, further comprising:

identifying the values within the program as partially constant values.

4). The method of claim 3, wherein the backward abstract semantic is for a

complex boolean function including $LEFT^{-1}$, $URIGHT^{-1}$, $JOIN^{-1}$, $MEET^{-1}$, LE^{-1}

and SRIGHT¹, and wherein the forward abstract semantic is for the complex boolean function including LEFT, URIGHT, JOIN, MEET, LE, and SRIGHT.

5). The method of claim 4, wherein the program is represented in an intermediate language.

6). The method of claim 5, wherein the implementation is a compiler for the programming language.

7). The method of claim 5, wherein the implementation is a computer aided design compiler for the programming language.

8). A computer-readable medium having stored thereon a plurality of instructions, said plurality of instructions when executed by a computer, cause said computer to perform:
 optimizing an implementation of a programming language, comprising;
 analyzing one or more values computed by a program written in the programming language, wherein analyzing one or more values comprises;
 representing each bit within a value of the one or more values as an abstract element of a lattice having a set of abstract elements including 0_A , 1_A , \perp_A and T_A , wherein the lattice is an abstraction of a concrete domain containing 0, 1, and \perp ;
 analyzing one or more output bits that are produced by an operation in terms of one or more input bits that are input to the operation; and
 analyzing the input bits that are input to the operation in terms of the output bits that are produced by the operation.

memory connected to the processor storing instructions for bidirectional
 bitwise constant propagation by abstract interpretation executed by the
 processor;
 storage connected to the processor that stores a software program having a
 plurality of separately compilable routines,
 wherein the processor optimizes an implementation of a programming
 language, by
 analyzing one or more values computed by a program written in the
 programming language, wherein analyzing one or more values
 comprises;
 representing each bit within a value of the one or more values as an
 abstract element of a lattice having a set of abstract elements
 including 0_A , 1_A , \perp_A and T_A , wherein the lattice is an abstraction of a
 concrete domain containing 0, 1, and \perp ;
 analyzing one or more output bits that are produced by an operation in
 terms of one or more input bits that are input to the operation; and
 analyzing the input bits that are input to the operation in terms of the
 output bits that are produced by the operation.

15). The system of claim 14, wherein the processor further optimizes by
 applying a forward abstract semantic to the abstract element; and
 applying a backward abstract semantic to the abstract element;
 wherein the forward abstract semantic is an approximation of a forward
 concrete semantic including AND, OR, and NOT; and
 wherein the backward abstract semantic is an approximation of a backward
 concrete semantic including AND^{-1} , OR^{-1} , and NOT^{-1} .

16). The system of claim 15, wherein the processor identifies the values within
 the program as partially constant values.

1 17). The system of claim 16, wherein the backward abstract semantic is for a
 2 complex boolean function including LEFT^{-1} , URIGHT^{-1} , JOIN^{-1} , MEET^{-1} , LE^{-1}
 3 and SRIGHT^{-1} , and wherein the forward abstract semantic is for the complex
 4 boolean function including LEFT , URIGHT , JOIN , MEET , LE , and SRIGHT .

1 18). The system of claim 17, wherein the program is represented in an
 2 intermediate language.

1 19). The system of claim 18, wherein the implementation is a compiler for the
 2 programming language.

1 20). The system of claim 19, wherein the implementation is a computer aided
 2 design compiler for the programming language.

1 21). A system, comprising:
 2 means for optimizing an implementation of a programming language,
 3 comprising;
 4 means for analyzing one or more values computed by a program written
 5 in the programming language, wherein analyzing one or more values
 6 comprises;
 7 means for representing each bit within a value of the one or more
 8 values as an abstract element of a lattice having a set of abstract
 9 elements including 0_A , 1_A , \perp_A and T_A , wherein the lattice is an
 10 abstraction of a concrete domain containing 0, 1, and \perp ;
 11 means for analyzing one or more output bits that are produced by an
 12 operation in terms of one or more input bits that are input to the
 13 operation; and

14 means for analyzing the input bits that are input to the operation in
15 terms of the output bits that are produced by the operation.

1 22). The system of claim 21, wherein the means for optimizing further
2 comprises:
3 means for applying a forward abstract semantic to the abstract element; and
4 means for applying a backward abstract semantic to the abstract element;
5 wherein the forward abstract semantic is an approximation of a forward
6 concrete semantic including AND, OR, and NOT; and
7 wherein the backward abstract semantic is an approximation of a backward
8 concrete semantic including AND⁻¹, OR⁻¹, and NOT⁻¹.

1 23). The system of claim 22, further comprising:
2 means for identifying the values within the program as partially constant
3 values.

1 24). The system of claim 23, wherein the backward abstract semantic is for a
2 complex boolean function including LEFT⁻¹, URIGHT⁻¹, JOIN⁻¹, MEET⁻¹, LE⁻¹
3 and SRIGHT⁻¹, and wherein the forward abstract semantic is for the complex
4 boolean function including LEFT, URIGHT, JOIN, MEET, LE, and SRIGHT.

1 25). The system of claim 24, wherein the program is represented in an
2 intermediate language.

1 26). The system of claim 25, wherein the implementation is a compiler for the
2 programming language.

1 27). The system of claim 26, wherein the implementation is a computer aided
2 design compiler for the programming language.